

Configuration of Parallels Mac Management Proxy Server fails

Parallels Device Management

Symptoms

- The following errors shown during the Parallels Mac Management Proxy configuration:
- pma_isv_proxy_config.log contains the following:

```
W /SqlClient:1860:884/ Query execution error: 'QSqlError(0, QODBC3:
Unable to execute statement, [Microsoft][ODBC SQL Server Driver][SQL
Server]Login MEDC\svc_Parallels not found. [Microsoft][ODBC SQL Server
Driver][SQL Server]User does not have permission to perform this
action. [Microsoft] [ODBC SQL Server Driver] [SQL Server]Login
MEDC\svc_Parallels doesn't map to any user. [Microsoft][ODBC SQL Server
Driver][SQL Server]Map login MEDC\svc_Parallels to user
pmmdbuser_ReadWrite. [Microsoft] [ODBC SQL Server Driver] [SQL
Server]User pmmdbuser_ReadWrite is a member of db_owner.)'
W /CmProxyCfgUtils:1860:884/ QSqlError(0, QODBC3: Unable to execute
statement, [Microsoft][ODBC SQL Server Driver][SQL Server]Login
MEDC\svc_Parallels not found. [Microsoft] [ODBC SQL Server Driver] [SQL
Server]User does not have permission to perform this action.
[Microsoft][ODBC SQL Server Driver][SQL Server]Login MEDC\svc_Parallels
doesn't map to any user. [Microsoft] [ODBC SQL Server Driver] [SQL
Server]Map login MEDC\svc_Parallels to user pmmdbuser_ReadWrite.
[Microsoft] [ODBC SQL Server Driver] [SQL Server] User pmmdbuser_ReadWrite
is a member of db_owner.)
F /pma_isv_proxy_config:1860:884/ Unable to configure PMM database.
```

Cause

Permissions issue.

Resolution

Grant the user account running the configuration wizard the SQL server role "db securityadmin"

© 2024 Parallels International GmbH. All rights reserved. Parallels, the Parallels logo and Parallels Desktop are registered trademarks of Parallels International GmbH. All other product and company names and logos are the trademarks or registered trademarks of their respective owners.